



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at www.mayerfabrics.com

CATEGORY

Panel

PROPERTIES



CONTENT

100% Recycled Polyester (25% Pre-/75% Post-Consumer)

BACKING

None

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-TEX

FINISH

None

WIDTH

66"

WEIGHT

12.1 oz./linear yard oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

58 yards

BREAKING STRENGTH

Warp 250/Fill 125

ABRASION RESISTANCE

N/A

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 3 min

COLORFASTNESS TO LIGHT

40 hours

FLAMMABILITY

Passes ASTM E84 Class 1 or A; Cal 117 Section E

WARRANTY

Panel | '5' Five Year Warranty



Eco System®

Sustainable. Attainable at Mayer Fabrics.

