



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at www.mayerfabrics.com

CATEGORY

Panel

PROPERTIES



CONTENT

54% Pre-Consumer Recycled Polyester/46% Polyester

BACKING

None

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-Tex

FINISH

None

WIDTH

66"

WEIGHT

10.5 oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

80 yards

VISUAL REPEAT

14.125 in/35.88 cm H, 12.25 in/31.12 cm V

BREAKING STRENGTH

Warp 100/Fill 100

ABRASION RESISTANCE

Passes 30,000 Double Rubs (Wyzenbeek)

COLORFASTNESS TO CROCKING

Dry: Class 4/Wet: Class 3.5

COLORFASTNESS TO LIGHT

60 hours

FLAMMABILITY

Passes ASTM E84 Class 1 or A (Unadhered); Cal 117 Section E

WARRANTY

Panel | '5' Five Year Warranty