
BASIC FOG
162-026

MAYERFABRICS



CLEANING
WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at www.mayerfabrics.com

CATEGORY
Panel

PROPERTIES

CONTENT
100% Recycled Polyester (65% Pre-/35% Post-Consumer)

BACKING
None

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)
Nano-Tex

FINISH
None

WIDTH
66"

WEIGHT
9.08 oz./ln yd

SHOWN RAILROADED
No

DIRECTIONAL
No

ROLL LENGTH
60 yards

BREAKING STRENGTH
Warp 266/Fill 244

SEAM STRENGTH
Warp: 55/Fill: 59

ABRASION RESISTANCE
N/A

COLORFASTNESS TO CROCKING
Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT
40 hours

FLAMMABILITY
Passes ASTM E84 Class 1 or A (Unadhered); Cal 117 Section E

WARRANTY
Panel | '5' Five Year Warranty

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.