



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at [www.mayerfabrics.com](http://www.mayerfabrics.com)

CATEGORY

Panel

PROPERTIES



CONTENT

66% Post-Consumer Recycled Polyester/34% Polyester

BACKING

None

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-Tex

FINISH

None

WIDTH

66"

WEIGHT

14.3 oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

50-60 yards

BREAKING STRENGTH

Warp 324/Fill 280

SEAM STRENGTH

Warp: 135/Fill: 140

ABRASION RESISTANCE

n/a

COLORFASTNESS TO CROCKING

Dry: Class 4/Wet: Class 4

COLORFASTNESS TO LIGHT

40 hours

FLAMMABILITY

Passes Cal TB 117-2013; ASTM E84 Class 1 or A (Unadhered)

WARRANTY

Panel | '5' Five Year Warranty