



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Additional cleaning details at [www.mayerfabrics.com](http://www.mayerfabrics.com)

CATEGORY

Panel

PROPERTIES



CONTENT

100% Recycled Polyester (65% Pre-/35% Post-Consumer)

BACKING

Acrylic

FINISH

None

WIDTH

66"

WEIGHT

10.37 oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

60 yards

VISUAL REPEAT

8.5 in/21.59 cm H, 33.103 in/84.08 cm V

BREAKING STRENGTH

Warp 205/Fill 137

SEAM STRENGTH

Warp: 11/Fill: 64

ABRASION RESISTANCE

PILLING RESISTANCE

Class 4

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 3 min

COLORFASTNESS TO LIGHT

40 hours

APPLICATION

Indoor

**FLAMMABILITY**

Passes Cal TB 117-2013; NFPA 260/UFAC Class 1; ASTM E84  
Class 1 or A (Unadhered)

**WARRANTY**

Panel | '5' Five Year Warranty