


BLUEPRINT DUSK

168-004

MAYER FABRICS



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Additional cleaning details at www.mayerfabrics.com

CATEGORY

Panel

PROPERTIES



CONTENT

100% Recycled Polyester (65% Pre-/35% Post-Consumer)

BACKING

Acrylic

FINISH

None

WIDTH

66"

WEIGHT

10.37 oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

60 yards

VISUAL REPEAT

8.5 in/21.59 cm H, 33.103 in/84.08 cm V

BREAKING STRENGTH

Warp 205/Fill 137

SEAM STRENGTH

Warp: 11/Fill: 64

ABRASION RESISTANCE

PILLING RESISTANCE

Class 4

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 3 min

COLORFASTNESS TO LIGHT

40 hours

APPLICATION

Indoor

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219

TOLL FREE: 800.428.4415 T: 317.267.2626 F: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.

As of: 4.26.2024

Page 1 of 2

FLAMMABILITY

Passes Cal TB 117-2013; NFPA 260/UFAC Class 1; ASTM E84
Class 1 or A (Unadhered)

WARRANTY

Panel | '5' Five Year Warranty