
CODE SUMAC
171-002

MAYERFABRICS



CLEANING
WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Additional cleaning details at www.mayerfabrics.com

CATEGORY
Panel

PROPERTIES

CONTENT
91% Recycled Polyester (59% Pre-/32% Post-Consumer)/9% Polyester

BACKING
Acrylic

FINISH
None

WIDTH
66"

WEIGHT
10.18 oz./ln yd

SHOWN RAILROADED
No

DIRECTIONAL
Yes

ROLL LENGTH
60 yards

VISUAL REPEAT
0.854 in/2.17 cm H, 0.188 in/0.48 cm V

BREAKING STRENGTH
Warp 195/Fill 87

SEAM STRENGTH
Warp: 10/Fill: 39

ABRASION RESISTANCE
n/a

PILLING RESISTANCE
Class 4

COLORFASTNESS TO CROCKING
Dry: Class 4 min/Wet: Class 3 min

COLORFASTNESS TO LIGHT
40 hours

APPLICATION
Indoor

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.

FLAMMABILITY
Passes Cal TB 117-2013; NFPA 260/UFAC Class 1; ASTM E84 Class 1 or A (Unadhered)

WARRANTY
Panel | '5' Five Year Warranty

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.