



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at www.mayerfabrics.com

CATEGORY

Upholstery & Panel

PROPERTIES



CONTENT

100% Polyester

BACKING

Acrylic

FINISH

Stain Repellent

WIDTH

54"

WEIGHT

12.1 oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

No

ROLL LENGTH

55 yards

BREAKING STRENGTH

Warp 395/Fill 298

SEAM STRENGTH

Warp: 81/Fill: 70

ABRASION RESISTANCE

Passes 183,000 Double Rubs (Wyzenbeek) Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

PILLING RESISTANCE

Class 5

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4

COLORFASTNESS TO LIGHT

40 hours

APPLICATION

Indoor

FLAMMABILITY

Passes Cal TB 117-2013; NFPA 260/UFAC Class 1; ASTM E84
Class 2 or B (Adhered)

WARRANTY

Standard Upholstery | '5' Five Year Warranty