



CLEANING

S: Solvent Cleaner - Spot clean, using a mild water-free solvent or dry cleaning product. Clean only in a well-ventilated room and avoid any product containing carbon tetrachloride or other toxic materials. Pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at www.mayerfabrics.com

CATEGORY

Upholstery & Panel

PROPERTIES



CONTENT

100% Polyester

BACKING

Acrylic

FINISH

Stain Repellent

WIDTH

54"

WEIGHT

13.06 oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

55 yards

BREAKING STRENGTH

Warp 377/Fill 116

SEAM STRENGTH

Warp: 65/Fill: 91

ABRASION RESISTANCE

Passes 237,000 Double Rubs (Wyzenbeek) Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

PILLING RESISTANCE

Class 5

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT

40 hours

APPLICATION

Indoor

FLAMMABILITY

Passes Cal TB 117-2013; NFPA 260/UFAC Class 1; ASTM E84 Class 1 or A (Unadhered); IMO A.652(16) 8.2

WARRANTY

Standard Upholstery | '5' Five Year Warranty