



CLEANING

S: Solvent Cleaner - Spot clean, using a mild water-free solvent or dry cleaning product. Clean only in a well-ventilated room and avoid any product containing carbon tetrachloride or other toxic materials. Pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at www.mayerfabrics.com

CATEGORY

Upholstery

PROPERTIES



CONTENT

57% Cotton/43% Polyester

BACKING

Latex

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-Tex, NanoGuard

FINISH

Nanotex®

WIDTH

54"

WEIGHT

12.64 oz./linear yard oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

60 yards

VISUAL REPEAT

14.38 in/36.53 cm H, 13.25 in/33.66 cm V

BREAKING STRENGTH

Warp 100/Fill 75

SEAM STRENGTH

Warp: 81/Fill: 50

ABRASION RESISTANCE

Passes 100,000 Double Rubs (Wyzenbeek) Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

PILLING RESISTANCE

Class 3

COLORFASTNESS TO CROCKING

Dry: Class 4/Wet: Class 3

COLORFASTNESS TO LIGHT

40 hours

FLAMMABILITY

Passes NFPA 260/UFAC Class 1; Cal 117 Section E; May comply with Cal. Tech. Bul. 133 when combined with appropriate components.

WARRANTY

Standard Upholstery | '5' Five Year Warranty



GREENGUARD
GOLD Certified

