
SOLEIL CORAL 416-009

MAYER FABRICS



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 parts bleach, 4 parts water = 20% bleach, 80% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 20% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Additional cleaning details at www.mayerfabrics.com

CATEGORY

Upholstery

PROPERTIES



CONTENT

59% Sunbrella® Solution-Dyed Acrylic/41% Sunbrella® Solution-Dyed Polyester

BACKING

None

FINISH

Sunbrella® Contract - PFOA & PFOS Free

WIDTH

54"

WEIGHT

13.9 oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

60 yards

VISUAL REPEAT

0 in/0.00 cm H, 0.125 in/0.32 cm V

BREAKING STRENGTH

Warp 305/Fill 219

SEAM STRENGTH

Warp: 40/Fill: 48

ABRASION RESISTANCE

Passes 100,000 Double Rubs (Wyzenbeek) Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

PILLING RESISTANCE

Class 4

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT

2000 hours

SOLEIL CORAL 416-009

MAYER FABRICS

APPLICATION

Atrium, Indoor, Outdoor

FLAMMABILITY

Passes NFPA 260/UFAC Class 1; Cal 117 Section E

WARRANTY

Standard Upholstery | '5' Five Year Warranty