
OPTIC 10 FIELDSTONE
424-017

MAYERFABRICS



CLEANING
WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at www.mayerfabrics.com

CATEGORY
Upholstery & Panel

PROPERTIES

CONTENT
83% Post-Consumer Recycled Polyester/17% Polyester

BACKING
Latex

FINISH
Stain Repellent

WIDTH
54"

WEIGHT
16.5 oz./ln yd

SHOWN RAILROADED
No

DIRECTIONAL
Yes

ROLL LENGTH
50-60 yards

VISUAL REPEAT
0.33 in/0.84 cm H, 0.2 in/0.51 cm V

BREAKING STRENGTH
Warp 359/Fill 315

SEAM STRENGTH
Warp: 60/Fill: 53

ABRASION RESISTANCE
Passes 185,000 Double Rubs (Wyzenbeek) Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

PILLING RESISTANCE
Class 4

COLORFASTNESS TO CROCKING
Dry: Class 4/Wet: Class 4

COLORFASTNESS TO LIGHT
40 hours

APPLICATION
Indoor

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.

FLAMMABILITY
Passes Cal TB 117-2013; NFPA 260/UFAC Class 1; ASTM E84 Class 1 or A (Unadhered)

WARRANTY
Spectrum Upholstery & Multi-Use Collection | '10' Ten Year Warranty

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.