SULA FLAME

MAYER FABRICS



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Additional cleaning details at www.mayerfabrics.com

CATEGORY

Upholstery

PROPERTIES



CONTENT

69% Sunbrella® Acrylic/31% Sunbrella® Polyester

BACKING

Acrylic Latex

FINISH

Liquid and Stain Repel - PFOA & PFOS Free

WIDTH

54"

WEIGHT

7.26 oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

50 yards

VISUAL REPEAT

7.03 in/17.86 cm H, 7.1 in/18.03 cm V

BREAKING STRENGTH

Warp 346/Fill 464

SEAM STRENGTH

Warp: 87/Fill: 78

ABRASION RESISTANCE

Passes 100,000 Double Rubs (Wyzenbeek) Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

PILLING RESISTANCE

Class 4 min

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT

2000 hours

APPLICATION

Atrium, Indoor, Outdoor

SULA FLAME 446-001

MAYER FABRICS

FLAMMABILITY

Passes Cal TB 117-2013; NFPA 260/UFAC Class 1

WARRANTY

Standard Upholstery | '5' Five Year Warranty