ANKARA STONE

622-010

MAYER FABRICS



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at www.mayerfabrics.com

CATEGORY

Upholstery

PROPERTIES # # * A

CONTENT

55% Acrylic/40% Polyester/5% Viscose

BACKING

Acrylic

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-Tex. NanoGuard

FINISH

Stain Repellent - PFOA Free

WIDTH

54"

WEIGHT

23.25 oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

55 yards

VISUAL REPEAT

14.17 in/35.99 cm H, 3.54 in/8.99 cm V

BREAKING STRENGTH

Warp 100/Fill 90

SEAM STRENGTH

Warp: 60/Fill: 80

ABRASION RESISTANCE

Passes 50,000 Double Rubs (Wyzenbeek)

PILLING RESISTANCE

Class 4

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT

40 hours

ANKARA STONE 622-010

MAYER FABRICS

APPLICATION

Indoor

FLAMMABILITY

Passes Cal TB 117-2013; NFPA 260/UFAC Class 1

WARRANTY

Standard Upholstery | '5' Five Year Warranty