ANKARA METAL
622-016

MAYERFABRICS



CLEANING
WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at www.mayerfabrics.com

CATEGORY
Upholstery

PROPERTIES

CONTENT
55% Acrylic/40% Polyester/5% Viscose

BACKING
Acrylic

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)
Nano-Tex, NanoGuard

FINISH
Stain Repellent - PFOA Free

WIDTH
54"

WEIGHT
23.25 oz./ln yd

SHOWN RAILROADED
No

DIRECTIONAL
Yes

ROLL LENGTH
55 yards

VISUAL REPEAT
14.17 in/35.99 cm H, 3.54 in/8.99 cm V

BREAKING STRENGTH
Warp 100/Fill 90

SEAM STRENGTH
Warp: 60/Fill: 80

ABRASION RESISTANCE
Passes 50,000 Double Rubs (Wyzenbeek)

PILLING RESISTANCE
Class 4

COLORFASTNESS TO CROCKING
Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT
40 hours

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.

APPLICATION
Indoor

FLAMMABILITY
Passes Cal TB 117-2013; NFPA 260/UFAC Class 1

WARRANTY
Standard Upholstery | '5' Five Year Warranty

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.