



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at [www.mayerfabrics.com](http://www.mayerfabrics.com)

CATEGORY

Upholstery

PROPERTIES



CONTENT

61% Polyester/30% Acrylic/9% Viscose

BACKING

Acrylic

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-Tex, NanoGuard

FINISH

Stain Repellent - PFOA Free

WIDTH

54"

WEIGHT

25.08 oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

55 yards

VISUAL REPEAT

2.875 in/7.30 cm H, 2.25 in/5.72 cm V

BREAKING STRENGTH

Warp 100/Fill 85

SEAM STRENGTH

Warp: 70/Fill: 80

ABRASION RESISTANCE

Passes 145,000 Double Rubs (Wyzenbeek) Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

PILLING RESISTANCE

Class 4

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT

40 hours

---

**APPLICATION**

Indoor

---

**FLAMMABILITY**

Passes Cal TB 117-2013; NFPA 260/UFAC Class 1

---

**WARRANTY**

Standard Upholstery | '5' Five Year Warranty

---