REFUGE SANDALWOOD
630-000

MAYERFABRICS



CLEANING
W: Water-Based Cleaner - Spot clean, using the foam only from a water-based cleaning agent, such as a mild detergent or non-solvent upholstery shampoo product. Apply foam with a soft brush in a circular motion. Always rinse promptly with clean water. Vacuum when dry. Pretest small area before proceeding.

Additional cleaning details at www.mayerfabrics.com

CATEGORY
Upholstery

PROPERTIES

CONTENT
51% Polyester/42% Acrylic/7% Viscose

BACKING
Acrylic

FINISH
Stain Repellent - PFOA & PFOS Free

WIDTH
54"

WEIGHT
23.74 oz./ln yd

SHOWN RAILROADED
No

DIRECTIONAL
Yes

ROLL LENGTH
~40 yards

BREAKING STRENGTH
Warp 90/Fill 120

SEAM STRENGTH
Warp: 120/Fill: 100

ABRASION RESISTANCE
Passes 85,000 Double Rubs (Wyzenbeek)

PILLING RESISTANCE
Class 4.5

COLORFASTNESS TO CROCKING
Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT
40 hours

APPLICATION
Indoor

FLAMMABILITY
Passes Cal TB 117-2013; NFPA 260/UFAC Class 1

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.

WARRANTY
Standard Upholstery | '5' Five Year Warranty

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.