



CLEANING

W: Water-Based Cleaner - Spot clean, using the foam only from a water-based cleaning agent, such as a mild detergent or non-solvent upholstery shampoo product. Apply foam with a soft brush in a circular motion. Always rinse promptly with clean water. Vacuum when dry. Pretest small area before proceeding.

Additional cleaning details at www.mayerfabrics.com

CATEGORY

Upholstery

PROPERTIES



CONTENT

51% Polyester/42% Acrylic/7% Viscose

BACKING

Acrylic

FINISH

Stain Repellent - PFOA & PFOS Free

WIDTH

54"

WEIGHT

23.74 oz./ln yd

SHOWN RAILROADED

No

DIRECTIONAL

Yes

ROLL LENGTH

~40 yards

BREAKING STRENGTH

Warp 90/Fill 120

SEAM STRENGTH

Warp: 120/Fill: 100

ABRASION RESISTANCE

Passes 85,000 Double Rubs (Wyzenbeek)

PILLING RESISTANCE

Class 4.5

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT

40 hours

APPLICATION

Indoor

FLAMMABILITY

Passes Cal TB 117-2013; NFPA 260/UFAC Class 1

WARRANTY

Standard Upholstery | '5' Five Year Warranty