CARESSA IVY
CA-133

MAYERFABRICS



CLEANING
CFC: Coated Fabrics Cleaning - When a spill/stain occurs wipe immediately with a clean dry cloth. Carefully remove the majority of the stain then follow the steps below.
Soap & Water - Remove ordinary dirt and smudges with a mild soap and water solution using a soft cloth or towel. Rinse with fresh water and wipe dry.
Non-abrasive Cleaners - If residue remains, use a straight application of the following cleaners: Fantastik or 409 and gently clean with a soft cloth. Rinse with fresh water and wipe dry.
Isopropyl Alcohol - More stubborn stains may be eliminated using a cotton cloth soaked in 70-91% isopropyl (rubbing) alcohol. Wipe without spreading stain to surrounding area. A second application should be applied with vigorous rubbing in a circular motion. For highly textured material, a soft brush is recommended to clean valleys and crevices. Rinse with fresh water and wipe dry.

BC: Bleach Cleanable - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Additional cleaning details at www.mayerfabrics.com

CATEGORY
Upholstery

PROPERTIES

CONTENT
80% Vinyl - Phthalate Free face, 20% Polyester backing

BACKING
100% Polyester

FINISH
Soil & Stain Resistant Top Coat with Ink Resistant Technology

WIDTH
54"

WEIGHT
29 oz./ln yd

SHOWN RAILROADED
No

DIRECTIONAL
No

ROLL LENGTH
30 yards

BREAKING STRENGTH
Warp 115/Fill 102

SEAM SLIPPAGE
Warp: 53/Fill: 50

ABRASION RESISTANCE
Passes 650,000 Double Rubs (Wyzenbeek) Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

COLORFASTNESS TO CROCKING
Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT
1000 hours

APPLICATION
Atrium, Indoor

FLAMMABILITY
Passes Cal TB 117-2013; NFPA 260/UFAC Class 1; AB 2998 Compliant; FMVSS 302

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.

WARRANTY
Standard Upholstery | '5' Five Year Warranty

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.