

# ETCH CHALK

## EH-037



**CATEGORY**  
Seating

**PROPERTIES**

**CONTENT**  
78% Vinyl face, 22% Polyester backing

**BACKING**  
Polyester

**FINISH**  
Soil & Stain Resistant Top Coat with Ink Resistant Technology

**WIDTH**  
54"

**WEIGHT**  
30 oz./linear yard

**SHOWN RR**  
No

**DIR**  
No

**ROLL LENGTH**  
30 yards

**VISUAL REPEAT**  
None

**BREAKING STRENGTH**  
Warp 101/Fill 93

**SEAM SLIPPAGE**  
Warp: 50 lbs. / Fill: 50 lbs.

**ABRASION RESISTANCE**  
Exceeds 100,000 Double Rubs (Wyzenbeek)

Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

**PILLING RESISTANCE**  
Class n/a

**COLORFASTNESS TO CROCKING**  
Dry: Class 4 min/Wet: Class 4 mi

**COLORFASTNESS TO LIGHT**  
300 hours

**APPLICATION**  
Indoor

**FLAMMABILITY**  
Passes Cal 117-2013; NFPA 260/UFAC Class 1; FMVSS 302; May comply with Cal. Tech. Bul. 133 when combined with appropriate components.

### CLEANING

**CFC: Coated Fabrics Cleaning** - Please refer to cleaning information section on Mayer website for complete cleaning info.

**BC: Bleach Cleanable** - 1 part bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean/disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)

**GREENGUARD**  
Certified

© Mayer Fabrics 2019

Specifications are subject to change. Current specifications are available at [mayerfabrics.com](http://mayerfabrics.com)  
Mayer Fabrics | 500 S. Kitley Ave, Indianapolis, IN 46219

TF. 800.428.4415  
T. 317.267.2626  
F. 317.267.2629