
# INTERLACE ALOE

# **MAYER** FABRICS



## CLEANING

CFC: Coated Fabrics Cleaning - When a spill/stain occurs wipe immediately with a clean dry cloth. Carefully remove the majority of the stain then follow the steps below.

Soap & Water - Remove ordinary dirt and smudges with a mild soap and water solution using a soft cloth or towel. Rinse with fresh water and wipe dry. Non-abrasive Cleaners - If residue remains, use a straight application of the following cleaners: Fantastik or 409 and gently clean with a soft cloth. Rinse with fresh water and wipe dry.

Isopropyl Alcohol - More stubborn stains may be eliminated using a cotton cloth soaked in 70-91% isopropyl (rubbing) alcohol. Wipe without spreading stain to surrounding area. A second application should be applied with vigorous rubbing in a circular motion. For highly textured material, a soft brush is recommended to clean valleys and crevices. Rinse with fresh water and wipe dry.

BC: Bleach Cleanable - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Additional cleaning details at www.mayerfabrics.com

CATEGORY Upholstery

PROPERTIES

**CONTENT** 70% Vinyl face, 30% Polyester backing

BACKING

100% Polyester

#### FINISH

Soil & Stain Resistant Top Coat with Ink Resistant Technology

**WIDTH** 54"

WEIGHT 30 oz./ln yd

30 02./iii yu

SHOWN RAILROADED No

# DIRECTIONAL

Yes

#### **ROLL LENGTH**

30 yards

BREAKING STRENGTH Warp 121/Fill 72

#### ABRASION RESISTANCE

Exceeds 100,000 Double Rubs (Wyzenbeek) Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

# COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4 min

#### COLORFASTNESS TO LIGHT 1000 hours

#### **APPLICATION**

Atrium, Indoor

## FLAMMABILITY

Passes Cal TB 117-2013; NFPA 260/UFAC Class 1; AB 2998 Compliant

#### WARRANTY

Standard Upholstery | '5' Five Year Warranty