



CLEANING

PC: Privacy Curtains Cleaning Info - Wash Cycle: Process Cubicle fabric as any ordinary colored fabric, temperature not to exceed 160F. Use a synthetic detergent. Add softener to the last rinse cycle. Extracting Cycle: Fabric requires no more than 2-4 min. extracting, depending on size of load and equipment used. Drying Cycle: Do not overload dryer. Tumble dry for 3-5 min. on synthetic cycle 110F. As with all polyester fabrics, excessive heat will detract from the permanent press characteristics of this fabric. Finishing: If fabric is folded upon completion of the drying cycle, no finishing is required. Occasional light touch-up with a hand iron (275F max), or using a flat bed press with covered head may be desired for smoother seams. Important: Use cover cloth between fabric and iron or pressing head. Avoid prolonged contact with heat. Notes: Do not use caustic soap or bleach. Do not put through a mangler.

Additional cleaning details at www.mayerfabrics.com

CATEGORY

Privacy Curtains

PROPERTIES



CONTENT

55% Recycled Polyester (27% Pre-/28% Post-Consumer)/45% FR Polyester

BACKING

None

FINISH

None

WIDTH

72"

WEIGHT

13.76 oz./ln yd

SHOWN RAILROADED

Yes

DIRECTIONAL

Yes

ROLL LENGTH

65 yards

VISUAL REPEAT

16.75 in/42.55 cm H, 18.376 in/46.68 cm V

BREAKING STRENGTH

Warp 204/Fill 221

SEAM STRENGTH

Warp: 78/Fill: 75

TEARING STRENGTH

Warp 18/Fill 40

WASHING PERFORMANCE

Appearance Retention: Class after 5
Shrinkage Retention: Less than 1% shrinkage after 5 Launderings

COLORFASTNESS TO WASHING

Class N/A

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 3 min

COLORFASTNESS TO LIGHT

40 hours

FLAMMABILITY

Passes Cal TB 117-2013; NFPA 260/UFAC Class 1; NFPA 701
(Test#1)

WARRANTY

Privacy Curtain | '3' Three Year Warranty