VECTOR SAPPHIRE
VE-014

MAYERFABRICS



CLEANING
WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

CFC: Coated Fabrics Cleaning - When a spill/stain occurs wipe immediately with a clean dry cloth. Carefully remove the majority of the stain then follow the steps below.
Soap & Water - Remove ordinary dirt and smudges with a mild soap and water solution using a soft cloth or towel. Rinse with fresh water and wipe dry.
Non-abrasive Cleaners - If residue remains, use a straight application of the following cleaners: Fantastik or 409 and gently clean with a soft cloth. Rinse with fresh water and wipe dry.
Isopropyl Alcohol - More stubborn stains may be eliminated using a cotton cloth soaked in 70-91% isopropyl (rubbing) alcohol. Wipe without spreading stain to surrounding area. A second application should be applied with vigorous rubbing in a circular motion. For highly textured material, a soft brush is recommended to clean valleys and crevices. Rinse with fresh water and wipe dry.

BC: Bleach Cleanable - 1 parts bleach, 4 parts water = 20% bleach, 80% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 20% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Write-Away products from Mayer Fabrics defies unsightly ink spots and paint stains. Take action 'right away' on Write-Away products by following the cleaning instructions for Ink Stains. Always rinse thoroughly with clean water.

Additional cleaning details at www.mayerfabrics.com

CATEGORY
Upholstery

PROPERTIES

CONTENT
40% Polyurethane Polycarbonate - PVC Free face, 60% Polyester backing

BACKING
Polyester

FINISH
WRITE AWAY® - Soil & Stain Resistant Top Coat with Ink Resistant Technology

WIDTH
54"

WEIGHT
16 oz./ln yd

SHOWN RAILROADED
No

DIRECTIONAL
Yes

ROLL LENGTH
40 yards

VISUAL REPEAT
20.25 in/51.44 cm H, 10.25 in/26.04 cm V

BREAKING STRENGTH
Warp 141.3/Fill 58.8

SEAM SLIPPAGE
Warp: 155.8/Fill: 124.7

ABRASION RESISTANCE
Exceeds 100,000 Double Rubs (Wyzenbeek) Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

HYDROLYSIS
10 weeks

COLORFASTNESS TO CROCKING
Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT
200 hours

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.

APPLICATION
Indoor

FLAMMABILITY
Passes Cal TB 117-2013; NFPA 260/UFAC Class 1; AB 2998 Compliant; IMO A.652(16) 8.2

WARRANTY
Standard Upholstery | '5' Five Year Warranty

500 S. KITLEY AVE., INDIANAPOLIS, IN 46219
TOLL FREE: 800.428.4415 **T**: 317.267.2626 **F**: 317-267-2629

© Mayer Fabrics 2024 Specifications are subject to change.